Electric Height Adjustable Desk 2-Leg

User Guide





IMPORTANT:

Any user or installer of desk base must study this manual carefully.

If this desk is sold, please provide the manual to the buyer.

TABLE OF CONTENTSPAGE				
1.	SAFETY AND WARNINGS	2		
2.	USAGE	2		
3.	SETUP AND INSTALLATION	2		
4.	PARTS LIST	3		
5.	ASSEMBLY INSTRUCTIONS	4		
6.	TECHNICAL SPECIFICATIONS	8		
7.	TROUBLESHOOTING GUIDE	8		

1. SAFETY AND WARNINGS

- Inappropriate use of this product may cause property or bodily injury.
- Check surroundings on all sides before using the desk. Body parts and property can be crushed if trapped between an immobile obstacle and the desk's range of motion.
- Ensure the length of power cords are accounted for when operating the desk. Monitors, computers, speakers, anything with a cord that is not long enough for the desk's range of motion could be pulled down or have its wires broken. Items pulled off the desk may cause other items to fall.
- Please provide this operation to any users, installers, or support personnel operating the product.

2. USAGE

This height adjustable desk has electric motors and is designed for use in dry work areas only. The desk height is adjustable so that it can be positioned at the most ergonomically suitable height. These desks are designed only for the purposes included in this manual. They should not be used in environments with high humidity or dampness. Any other use is at user's risk.

Do not move around, crawl or lie under the desk frame. Do not sit or stand on the desk frame.

Children should never use the desk unless they are supervised by adults.

Liability: Under no circumstances does the manufacturer accept warranty claims or liability claims for damages caused from improper use or handling of the desk frame other than that which is described in this operation manual.

3. SETUP AND INSTALLATION

Once the desk has been assembled, adjust the feet so that the desk is level and does not shift its position. After this, connect the desk to the 110v or 220v outlet and the desk is ready for use.

Check that no cables can get jammed.

Choose a placement for the desk that's a safe distance from window frames, radiators, furniture etc. so that people do not get stuck or trapped by the desk.

Do not place any objects that are taller than 50cm(20") underneath the desk. After it has been assembled, when moving the desk, DO NOT lift the desk by the desktop. Lifting this way can stress the fasteners connecting the desk base to the desktop. Lower the desk completely and lift the desk by grabbing the top of the desk base or by removing the desktop first.

PARTS LIST 4.



Please count all pieces before disposing of any carton or packing material. Use a padded or carpeted area for assembly to avoid damage. For ease and safety, we recommend two people for assembly.



Part #	Description	Qty
0	Leg	2
2	Foot	2
3	Crossbar End	4
4	Crossbar Center Rail	3
6	Side Bracket	2
6	Control Box	1
7	Handset	1
8	Leveling Studs	4
9	Wires (Power & Connector wires)	2
D	M6x12 Machine Screw	28
0	M8x10 Machine Screw	6
	M8 Nut	2
Ð	M 5x18 Pan Head Screw	10
ß	Cable Clips	5
14	Washers	10
Ð	M4x12 Pan Head Screw	2
16	Adjustable frame	1
Ð	M6x16 Machine Screw	8

5. ASSEMBLY INSTRUCTIONS

First, Lay out all components and hardware to ensure that you have all the parts listed on the Α. components list. Then Slide Crossbar Center Rails (Part #4) out of Crossbar Ends (Part #3).



Line up the holes on each Leg (Part #1) with the holes on each Crossbar End (Part #3).

B. IMPORTANT! DO NOT TIGHTEN SCREWS IN THIS STEP, ONLY INSERT THEM AND ROTATE 3 TIMES. YOU WILL TIGHTEN IN STEP D.

Insert gty 4 Machine Screws (Part #10) through the 2 holes of each Crossbar End (Part #3) going into the Leg (Part #1). Using the Allen Wrench, rotate each screw ONLY 3 times.



C. IMPORTANT! DO NOT TIGHTEN SCREWS IN THIS STEP, ONLY INSERT THEM AND ROTATE 3 TIMES. YOU WILL TIGHTEN IN STEP D.

Line up the 2 holes on the Side Brackets (Part #5) with the Crossbar End and Leg assembly from the previous step.

Insert gty 4 Machine Screws (Parts# 10) through the 2 holes of the Side Bracket (Part #5) going into the Crossbar End/Leg Assembly. Using the Allen Wrench, rotate each screw ONLY 3 times.

If you are having trouble getting all the screws started, it is because other screws are too tight. You'll need to back out some screws in order to loosen the tolerance of the screw holes.



3

D. Once all of these screws have been started, you can now tighten the qty 4 Machine Screws (Part #11) from Step C and the gty 8 Machine Screws (Part #10) described in Step B (12 screws in total).

Ε. The Crossbar Center Rails (Part #4) are optional. They provide more stability but if not needed they can be skipped during installation

or removed later. Slide Crossbar Center Rails (Part #4) back into Crossbar Ends (Part #3). Ensure the slots of the Crossbar Center Rails are facing inward. 4

F. Attach each Foot (Part #2) with qty 4 Hexagon \mathfrak{o} cket(Part #1 \mathfrak{J} and tighten bolts in a cross pattern.

G. Your desktop may or may not be pre-drilled. Please check both sides of the desktop before placing the desk base on it for pre-drilling! Carefully place the upside down desk base on the underside of the desktop.

Note: minimum top size: 110cm(43")wide x 60cm(24")deep Adjust the width of the base to fit the desktop by sliding the two halves outward. 101cm(40") to 174 cm(68.5") max.

Place the base where you want it. Some will want the frame to be all the way to the edge of the desk. We recommend leaving at least 5cm(2") of desktop width (on each side) protruding beyond the frame width.

Center the frame by using the desktop edge as a reference. Measure to the metal brace. Do not use the screw holes as a point of reference.



Η. Secure the Center Rails at both ends using qty 14 Machine srews(Part #1 0), qty 4 per side.



Ensure that the screw hits the metal center rail by sliding the center rail as needed.



Ι. Double-check that the base is centered on the underside of the desktop and is located where you want it. Also, double-check that the included wood screws are not too long for your desktop and won't puncture the surface when screwed all the way in.



We recommend you pre-drill any holes needed for fasteners connecting the base to the top. NOTE: PLEASE ENSURE THAT YOUR DESKTOP DOES NOT ALREADY HAVE HOLES BY CHECKING BOTH SIDES. This will make it easier to attach the screws

and will greatly lessen the stress caused by driving a screw into the desktop material.

Now, proceed with securing the desk base to the desktop using gty 10 of the Pan Head Screws (Part #12).

Install as follows: 4 per Side Bracket (left) 4 per Side Bracket (right) 1 per Crossbar End (left) 1 per Crossbar End (right)

Never use countersunk screws to fasten into the desktop. This will cause much greater stress on the desktop. Ensure any screw used will not puncture through the desktop surface or otherwise damage the material.



J. IN THIS FOLLOWING STEP, DO NOT OVERTIGHTEN SCREWS. OVER TIGHTENING COULD CAUSE THE PLASTIC ON THE COMPONENTS TO BREAK.



We recommend you pre-drill any holes needed for fasteners connecting the Control Box to the top. This will make it easier

to attach the screws and will greatly lessen the stress caused by driving a screw into the desktop material.

Never use countersunk screws to fasten into the desktop. This will cause much greater stress on the desktop. Ensure any screw used will not puncture through the desktop surface or otherwise damage the material.

Insert hie Control bx nito hie coss backet Part#3) which has hie abs. Ensure eough bearance talte wire prts of rable onnections.



K. IN THIS FOLLOWING STEP, DO NOT OVERTIGHTEN SCREWS. OVER TIGHTENING COULD CAUSE THE PLASTIC ON THE COMPONENTS TO BREAK.

Place the Handset (Part #7) so the front of the Handset runs flush with the desktop edge. The Handset can be placed anywhere along the front edge of the desk, but we recommend placing it near the side so it doesn't interfere with your chair or legs when seated. Use qty 2 of the Pan Head Screws (Part #1 5) to attach the Handset (Part #7) to the desktop.

L. Connect the Wires as per the diagram below. Use the adhesive-backed Cable Clips (Part #1 3) to secure the Connecting Wires, so they don't sag.



M. Turn the assembled desk right-side-up. With two people, grab the desk by the base (not the desktop) and turn the desk right-side up. Adjust the Leveling Studs on the Feet (Part #2) as needed.



N. Plug the Power Cord into a 110v or 220v outlet. *IMPORTANT!*

You must RESET the desk prior to use:

Press and hold the DOWN button on the Handset (Part #7) until the desk reaches its lowest height. Release the DOWN button. Press and hold the DOWN button again for about 10 seconds until the desk lowers a little bit more, slightly rises and stops. Release the DOWN button.



Your desk is now ready to use.

To program up to four presets:

Use the up/down buttons to find a desired height, then press "M" followed by a number 1 - 4.

6. <u>TECHNICAL SPECIFICATIONS</u>

Height Range	75cm(2 9.5) – 120cm (47.2)		
Base Width	101cm (40") min – 1 80cm (71") max		
Travel Speed	7mm (0.28) per second		
Weight Capacity	360kg (794bs).		
Duty Cycle	10%, Max. 2 mins on, 18 mins off		
	4 Memory presets		
	Soft Start/Stop		
	Adjustable leveling studs		

7. TROUBLESHOOTING

--Reset Instructions--

If experiencing error messages showing on the Handset or no response when trying to raise or lower:

Unplug he power able and pug ord back ni, Reset by bilding down button ofr 5seconds. The elsk will erach the olivest beight and bightly inses and bops. (buzzer will ermind by bee which means reset bave infished)

If he elsk cashed nito else hito els

If the handset displays E11 or E21, confirm that all wired connections are secure (legs to cables, cables to control box). Then perform the reset procedure above. If the error message persists after the reset procedure or if the height between the legs exceeds 5 cm (2inches) stop the reset procedure and contact us or local distributors.

If the landset displays HOT", et the lase erst and ool of wn ofr 20 minutes.

If the desk seems to be uneven, try the reset instructions above. If that does not work you may need to adjust the levelers at the bottom of the foot.



In the event of a power outage or if the power cord is unplugged, a manual reset may be necessary (see Reset Instructions above)



This product is designed with a duty cycle of 10% (2 min. on, 18 min. off)





Keep Children away from electric height-adjustable desks, control units and handsets. There is a risk of injury and electric shock



Do not open any of the components: lifting columns, control box, or handset. There is a danger of electric shock



Keep all electrical components away from liquids