

intra●se



THE NEW **EDGE**



| | |
|---------------------------------------|------------|
| Item No | 1415045117 |
| Identification | PTE15N |
| Capacity Kg | 1500 |
| Min fork height mm | 80 |
| Lifting height mm | 115 |
| Fork width mm | 540 |
| Total width mm | 540 |
| Fork length mm | 1150 |
| Total length mm | 1530 |
| Driving speed with/without load km/h | 4.6/4.8 |
| Lifting speed with/without load mm/s | 20/25 |
| Lowering speed with/without load mm/s | 50/40 |
| Turning radius mm | 1330 |
| Drive motor | 0.65 kW |
| Lifting motor | 0.50kW |
| Battery V/Ah | 24/20 |
| Charger | External |
| Fork wheel Ø mm Polyurethane | 80 x 93 |
| Drive wheel Ø mm | 210 x 70 |
| Weight kg incl. battery | 123 |

THE NEW MODEL - EDGE!

Smart Design, Rubust, Safe, Ergonomic and Maintenance Friendly!

The new model of electric pallet truck combines the advantages of manual and electric pallet trucks being the perfect electrical product for light and medium duty material transportation in most effortless and econmic way!

EDGE

SWEDMACH



DRIVE WITH HANDLE IN VERTICAL POSITION

The function of driving with tiller in the **VERTICAL POSITION** helps with work in confined areas, especially in elevators and lorries without sacrificing of safety.



MAINTENANCE-FREE LITHIUM BATTERY

The EDGE is equipped with maintenance-free lithium battery with 24V/20Ah and a weight of only 4kg. Very easy to remove and charge.



ROBUST & SMART DESIGN OF CHASSIS

Strong and compact structure of chassis helps to ensure long lifetime of the truck, without sacrificing the truck's weight or putting under question the strength of frame.

